Technical Sprays
**Lubricating and Multifunctional Oils**

# Pneuma-Lube




## Lubricant for pneumatic equipment | high content of PTFE

As a lubricating and corrosion protection agent, WEICON Pneuma-Lube is the universal problemsolver for all moving parts in pneumatic equipment and accessories. Its special product formula with a high content of PTFE makes it a multi-purpose product for: lubrication, corrosion protection, cleaning, water displacing and conservation. The product can not only be used in installation or maintenance of pneumatic equipment and accessories, but also on pneumatic tools in operation. Its excellent weathering resistance allows its use in other sectors as well, e.g. in the on- and offshore industry.

### Application

Shake can well and apply from a distance of approx. 5 cm, then allow to take effect for approx. 30 seconds.

### Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

### Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

### Available sizes

10010547 Pneuma-Lube, 400 ml, yellowish

**Technical data**

| | | |
|---|---|---|
| Odour | | vanilla |
| Colour | | yellowish |
| Specific properties | | with PTFE |
| Silicone-free | | yes |
| Minimum shelf life | at room temperature | 24 mon. |
| Kinematic viscosity (40°C) | | 21 $mm^2/s$ |
| Kinematic viscosity (100°C) | | 4 $mm^2/s$ |
| Temperature resistance | | -50°C to +210°C |
| Compatible with Double Nozzle | | yes |

**Approvals / Guidelines**

| | |
|---|---|
| IMPA Code | 450825 |

To the product detail page:

Note
The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquaters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Colombia S.A.S
Colombia
Phone: +57 314 793 86 06
Email: info@weicon.co

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.L.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr