Technical Liquids
Dosing and Processing Tools

Pump Dispenser WPS 1500



Refillable spray dispenser made of plastic

WPS 1500 is a refillable pump dispenser. The build-up of pressure in the fluid container is achieved by pumping pure air with the pump rod. An integrated security valve opens automatically as soon as the allowed pressure (max. 4 bar) has been exceeded. Pushing the spray lever provides an even and constant fluid emission. By turning the spray adjustment dial, the spray rate and spray pattern can be adjusted from a strong jet to a light spray mist.

Technical Data		
Filling quantity		1.300 ml
Container volume		1.500 ml
Operating pressure		< 4 bar
Characteristics		
Specific properties		refillable plastic sprayer
Minimum shelf life	at room temperature	∞ mon.
Width		130
Approvals / Guidelines		
ISSA Code		75.628.13

Application

WPS 1500 is suitable for:

- Cutting Fluid
- Anti-Spatter
- Brake Cleaner
- Corro-Protection
- Citrus Cleaner
- Stainless Steel Polish
- Electro Contact Cleaner
- Label Remover
- Mould Cleaner
- Mould Release Agent
- Leak Detection
- Leak Detection frost-proof
- Leak Detection viscous
- Metal-Fluid
- Surface Cleaner
- Plastic Cleaner
- Pneuma-Lube
- Cleaner S
- Fast Cleaner
- Silicone
- Parts and Assembly Cleaner
- Workshop Cleaner

WPS 1500 with Viton seal is suitable for:

- AT-44
- Rust Loosener
- W 44 T

Note
The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquaters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Colombia S.A.S
Colombia
Phone: +57 314 793 86 06
Email: info@weicon.co

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.L.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr

Technical Liquids
Dosing and Processing Tools

Pump Dispenser WPS 1500

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Accessories

10016213 Extension tube for WPS 1500, 1 PCE
10023969 WEICON Set of O-Rings Viton, 1 PCE, black

Available sizes

de-DE;en-SG;es-UY;en-ZA;tr-TR;de-CH;sk-SK;it-IT;en-AU;en-AE;ko-KR;hu-HU;cs-CZ;pl-PL;nl-NL;nl-BE;fr-FR;fr-BE;ro-RO;es-ES;pt-PT;en-CA;de-AT;en-US

Available sizes:

1 PCE

Conversion table

(°C x 1.8) + 32 = °F
mm/25.4 = inch
µm/25.4 = mil
N x 0.225 = lb
N/mm^2 x 145 = psi
MPa x 145 = psi
Nm x 8.851 = lb·in
Nm x 0.738 = lb·ft
Nm x 141.62 = oz·in
mPa·s = cP
N/cm x 0.571 = lb/in
kV/mm x 25.4 = V/mil

To the product detail page:

Note
The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquaters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Colombia S.A.S
Colombia
Phone: +57 314 793 86 06
Email: info@weicon.co

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.L.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr